



DESCRIPTION

Item 40-41- Suspended structural glass facade with load bearing vertical profiles of the nominal width of 60 mm and a depth of 158 mm

- The secondary horizontal profiles of the nominal width of 60 mm, and the depth of 116 mm
- Coefficient of heat transfer through the bundle of the profiles $U_f = 1.6 \text{ W / m}^2\text{K}$
- All panels are glazed with structural glass ,
- Item contains 5 panels that are opened according to the scheme, and 11 fixed panels
- Dimensions of the item 100x1925cm

The whole item is to be ordered in consultation with the designer and the investor, and made and installed following the instructions of the selected manufacturer.

All measures are to be checked on the spot.

OPIS

Ovješena strukturalna staklena fasada sa nosivim vertikalnim profilima nazivne širine 60 mm i dubine 158 mm

- sekundarni horizontalni profili nazivne širine 60 mm, a dubine 116 mm
- koeficijent prolaza toplote kroz snop profila $U_f=1,6 \text{ W/m}^2\text{K}$
- 14 polja ostakljena strukturalnim staklom
- 2 polja u nivou prizemlja ostakljena sigurnosnim strukturalnim staklom
- pozicija sadrži 5 polja koja se otvaraju prema šemi i 11 fiksnih polja
- dimenzije pozicije 100x1925cm

Cijelu poziciju naručiti u dogovoru sa projektantom i investitorom, a izraditi i ugraditi prema uputama odabranog proizvođača.

Sve mjere provjeriti na licu mjesta.