



DESCRIPTION

Item 43- Suspended structural glass facade with load bearing vertical profiles of the nominal width of 60 mm and a depth of 158 mm

- The secondary horizontal profiles of the nominal width of 60 mm, and the depth of 116 mm
- Coefficient of heat transfer through the bundle of the profiles  $U_f = 1.6 \text{ W / m}^2\text{K}$
- All panels are glazed with structural glass ,
- Item contains 10 panels that are opened according to the scheme, and 22 fixed panels
- Dimensions of the item 205x1925cm

The whole item is to be ordered in consultation with the designer and the investor, and made and installed following the instructions of the selected manufacturer.

All measures are to be checked on the spot.

OPIS

Ovješena strukturalna staklena fasada sa nosivim vertikalnim profilima nazivne širine 60 mm i dubine 158 mm

- sekundarni horizontalni profili nazivne širine 60 mm, a dubine 116 mm
- koeficijent prolaza toplote kroz snop profila  $U_f=1,6 \text{ W/m}^2\text{K}$
- sva polja ostakljena strukturalnim staklom
- pozicija sadrži 10 polja koja se otvaraju prema šemi i 22 fiksnih polja
- dimenzije pozicije 205x1925cm

Cijelu poziciju naručiti u dogovoru sa projektantom i investitorom, a izraditi i ugraditi prema uputama odabranog proizvođača.

**Sve mjere provjeriti na licu mjesta.**